Elammer's Copy

106:37211 HCA AN

Free-cutting copper alloys having low oxygen content ΤI

Nishikiori, Kiyoaki; Kimura, Atsuyoshi IN

Daido Steel Co., Ltd., Japan PA

Jpn. Kokai Tokkyo Koho, 3 pp. SO

CODEN: JKXXAF

Patent DT

Japanese LA

FAN.CNT 1

APPLICATION NO. DATE KIND DATE PATENT NO.

19841201 JP 1984-252826 19860620 A2 JP 61133351 ΡI

The Cu alloys contain .gtoreq.1 of Pb, Bi, and/or Te AB 0.05-1% each, and .gtoreq.1 of Ni, Sn, and/or Sb 0.01-0.5% each. Cu alloys show good hot workability, and are useful for elec. and electronic parts. Thus, molten cu alloy refined in vacuum was cast into 30-kg ingot contg. 0.1 Ni, 0.2% Pb, and .ltoreq.10 ppm O. The ingot showed good forging at 700-800.degree.,

drill cutting torque 0.02 kg-m in a test with drill diam. 3 mm at 0.1 mm/rev and

cutting speed 15 m/min, and elec. cond. 96% of IACS, vs. good forgeability, 0.06 kg-m, and 100 for Cu contg. O .ltoreq.10 ppm.